

INFORMATION

1. THE COVERS ARE RECESSED TO ACCEPT A SCREED WITH A TILE OR RESIN FLOOR FINISH.
2. INSTALLED, THEY GIVE AN AESTHETIC APPEARANCE LEAVING ONLY THE POLISHED PERIMETER EDGE BAR VISIBLE, LOCKABLE AND DOUBLE SEALED.
3. COVERS ARE REMOVED FOR ACCESS BY REPLACING THE HOLDING DOWN BOLTS WITH THE THREADED LIFTING HANDLES SUPPLIED.
4. THE 4200 COVERS ARE SUPPLIED AS INDIVIDUAL OR MULTIPLE UNITS.
5. MULTIPLE COVERS CAN BE USED IN CONJUNCTION WITH A STAINLESS STEEL CHANNEL TO FORM A CONTINUOUS DUCT.
6. LOADING CAPACITIES ARE PEDESTRIAN. SPECIALLY DESIGNED HEAVY-DUTY COVERS ARE AVAILABLE ON REQUEST.
7. AVAILABLE IN GRADE 304 OR 316 STAINLESS STEEL.

MATERIAL SPECIFICATION:

STAINLESS STEEL - GRADE 304 (BS 1449:PART 2:1983) 1.4301 (BS EN 10088-1:1995)
 STAINLESS STEEL - GRADE 316 (BS 1449:PART 2:1983) 1.4436 (BS EN 10088-1:1995) - ALTERNATIVE OPTION

INSTALLATION INSTRUCTIONS

1. CAREFULLY UNLOAD THE ASSEMBLED COVER AND REMOVE PACKAGING MATERIAL.
2. FIT THE OUTER FRAME OVER THE MANHOLE AND ADJUST TO FINISHED FLOOR LEVEL.
3. FIX AND BED-IN THE OUTER FRAME.
4. LOCATE THE RECESSED COVER IN THE FRAME, SECURING IN POSITION WITH SUPPLIED FIXINGS.
5. FILL WITH SUITABLE INFILL LEAVING ADEQUATE RECESS FOR FLOOR FINISH, BUT ENSURING NO CAVITIES ARE PRESENT WHICH WILL AFFECT THE STRUCTURAL INTEGRITY OF THE COVER. FINALLY, APPLY FLOOR FINISH.
- 6.

CONTACT DETAILS:

COMPONENT DEVELOPMENTS

**HALESFIELD 10
 TELFORD
 SHROPSHIRE
 TF7 4QP**

**T: 01952 588488
 F: 01952 684395**

**E-MAIL: Info@componentdevelopments.com
 WEBSITE: www.componentdevelopments.com**

APPROXIMATE WEIGHT:

COVER & FRAME ASSY (UNFILLED):
 600 x 600mm C/O = 23kg
 600 x 750mm C/O = 29kg

COVER ONLY
 (CW INFILL TYP. C35 CONCRETE):
 600 x 600mm C/O = 65kg
 600 x 750mm C/O = 81kg

PLEASE NOTE: ALL LIFTING OF COVERS SHOULD BE UNDERTAKEN FOLLOWING CURRENT HEALTH & SAFETY LEGISLATION PRACTISES.

REPLACEMENT PARTS:

PLEASE CONTACT US DIRECTLY FOR ALL REPLACEMENT PARTS, FULL TECHNICAL ASSISTANCE CAN BE PROVIDED.

DATA SHEET

TYPE 4200

**STAINLESS STEEL
 RECESSED MANHOLE COVER**

